Easy~Fit - Cantilever Arms



Easy~Fit Cantilever Arms

These ready-made, hot-dipped galvanised steel cantilever arms with 14mm diameter holes, offer a quick and easy method of supporting condensing units on external walls. Available in a straight length and webbed version in a variety of lengths. The strut dimensions are 41mm x 41mm x 2.5mm.

Features

- Low cost mounting option
- Available in single, double and webbed versions
- Strut dimensions are 41mm x 41mm x 2.5mm
- Hot Dip Galvanised

The Package

- sold as singles
- 2 x cantilever arms for the kit webbed / single or double

Related Products

End Caps Fixings Drip Trays Cantilever Arm Kits

| Part Code | Description | Safe Working Load* | Length | Weight |
|-----------|-------------------------------|--------------------|--------|--------|
| CA-150-S | Cantilever Arm – Single 150mm | 250kg | 150mm | 0.8kg |
| CA-300-S | Cantilever Arm – Single 300mm | 250kg | 300mm | 1kg |
| CA-450-S | Cantilever Arm – Single 450mm | 250kg | 450mm | 1.4kg |
| CA-600-S | Cantilever Arm – Single 600mm | 190kg | 600mm | 2kg |
| CA-750-S | Cantilever Arm – Single 750mm | 150kg | 750mm | 2.4kg |
| CA-900-S | Cantilever Arm – Single 900mm | 120kg | 900mm | 3.0kg |
| CA-600-W | Cantilever Arm – Webbed 600mm | 190kg | 600mm | 2.6kg |
| CA-750-W | Cantilever Arm – Webbed 750mm | 150kg | 750mm | Зkg |
| CA-600-D | Cantilever Arm – Double 600mm | 243kg | 600mm | 3.7kg |
| CA-750-D | Cantilever Arm – Double 750mm | 205kg | 750mm | 4.5kg |
| CA-900-D | Cantilever Arm – Double 900mm | 140kg | 900mm | 5.6kg |

The safe working loads quoted are for a concentrated load located at the mid-point of the arm.

* It is the installer's responsibility to ensure that equipment weights do not exceed the safe working loads quoted

The Pump House sales team are available to answer your questions or queries on this product. Our experts are waiting for your call **+44 (0)115 900 5858** or if you prefer send an email to **sales@pumph.co.uk** or visit **www.pumph.co.uk**

