

Model: AHC2466ZKZ
Product Description

Type: Reciprocating Compressors
Application: LBP - Low Back Pressure
ProductDescription: R-404A
Voltage/Frequency: 220V 3~ 60Hz 220V 3~ 50Hz
Version: N/A


Product Specifications
Performance

| Condition | Test Voltage | Refrigeration Capacity | | | Input Power (I) W | (E) Efficiency | | | EVAP TEMP | Condition | AMBIENT TEMP | RETURN GAS | LIQUID TEMP |
|-----------|--------------|------------------------|---------------|----------|----------------------|----------------|----------------|-----|---------------|--------------|-----------------|---------------|----------------|
| | | (R) Btu/h | (R) kcal/h | (R) W | | (E) Btu/Wh | (E) kcal/Wh | W/W | | | | | |
| EN12900 | 220V 3~ 50HZ | 2983 | 752 | 874 | 1146 | 2.6 | .66 | .76 | -35°C (-31°F) | 40°C (104°F) | 32°C (90°F) | -25°C (-13°F) | 40°C (104°F) |

General

Evaporating Temp. Range: -40°C to -12.2°C (-40°F to 10°F)
Motor Torque:
Compressor Cooling:

Mechanical

Weight: 33
Weight Unit of Measure: KG
Displacement (cc): 53.2
Oil Type:
Viscosity (cSt):
Oil Charge (cc): 0

Electrical

Voltage Range (50 Hz):
Voltage Range (60 Hz):
Locked Rotor Amps (LRA): 0
Rated Load Amps (RLA 50 Hz): 5.2
Rated Load Amps (RLA 60 Hz): 5.2
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 1.82

Motor Resistance (Ohm) - Start:
MotorType:

Overload Type:

Relay Type:

Agency Approval

CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed, SASO Listed, UL Recognized, cURus Recognized